

STULZ

CLIMATE. CUSTOMIZED.



An efficient way to optimum air quality

Optimize processes, save energy, ensure quality –
with Stulz UltraSonic air humidifying systems

STULZ UltraSonic – the humidifying system with maximum energy efficiency

In computer rooms, laboratories, equipment rooms, hospitals and offices – humidification is a vital element of optimum air conditioning everywhere. For printing presses, lithographers, photo labs and electronics factories, made-to-measure humidifier solutions ensure highly efficient production. Humidification also plays an important role in the leather and textile industry. In baking firms and cheese factories, in warehouses for fruit and

vegetables and in food counters, humidification preserves quality and optimizes the production process. In all these cases, STULZ UltraSonic humidifying systems provide tailor-made humidification, ensuring optimum processes and high quality standards.

The STULZ UltraSonic system is available in different versions, e.g. for direct room installation or fitting in an air duct.






Adiabatic humidification

The energy required for the adiabatic humidification process is removed from the air as heat energy, and a cold mist is produced that humidifies the room.

This change of state is clearly illustrated in the h,x diagram.



Example:

Air at 21 °C / 3 g/kg is humidified to 7 g/kg.

Advantages at a glance

Maximum energy savings

STULZ UltraSonic uses up to 93 % less electricity than electrode/resistance steam humidifiers with the same capacity.

Excellent control characteristics

Full humidifier capacity is available without delay as soon as the unit is switched on, and humidification stops as soon as the unit is switched off.

Energy-saving cooling effect

Due to the laws of physics, room humidification with STULZ UltraSonic also cools the room. This considerably reduces the running time of the compressors when air conditioning units are used at the same time.

Efficient control technology/flexible MSR integration

Different control modules ensure optimum integration of STULZ UltraSonic humidifiers for every type of project.

Short humidification distance

The water particles measure just 0.001 mm on average. This very fine mist is absorbed by the air straight away.

Long service life

The principal components of STULZ UltraSonic humidifying systems are made of stainless steel or high-grade plastic. The oscillators have a minimum running time of 10,000 operating hours at nominal capacity.

Rapid payback/future-proof investment

STULZ UltraSonic humidifying systems pay for themselves within a very short time. In the face of rising energy prices, the STULZ UltraSonic system is a future-proof investment!

Hygienic humidification

Thanks to a continual supply of fresh water (no recirculating water!) and a special purging or flushing cycle, humidification is always perfectly hygienic.





STULZ UltraSonic ENS humidifiers for duct installation

Units from the STULZ UltraSonic ENS model series are available for use in ventilation and air conditioning systems. They can be installed in ventilation ducts, box-type units, and air conditioning units, for example. Units from the modular ENS 1200 A to ENS 9600 A series are made of high-grade plastic. The ENS 14 A/18 A models are available in a stainless steel casing. Since the units can be installed directly in an air duct, for example, no internal fan

is required either – the airflow in the duct is all that is needed to transport the mist out of the humidifier. Tried and tested controller components ensure that the desired room humidity is precisely maintained. This system is used in all properties where a ventilation system is installed, and where optimum humidity is essential for production, storage or the room climate.



ENS humidifiers for integration

Model	Humidifier capacity (kg/h)	Number of oscillators	Dimensions H x W x D (mm)	Power consumption (W)	Weight without water (kg)
ENS 1200 A	1.2	2	157 x 220 x 145	65	1.5
ENS 2400 A	2.4	4	157 x 340 x 145	125	2.2
ENS 3600 A	3.6	6	157 x 460 x 145	185	2.9
ENS 4800 A	4.8	8	157 x 580 x 145	240	3.6
ENS 6000 A	6.0	10	157 x 700 x 145	310	4.3
ENS 7200 A	7.2	12	157 x 820 x 145	375	5.1
ENS 8400 A	8.4	14	157 x 940 x 145	435	5.8
ENS 9600 A	9.6	16	157 x 1,060 x 145	495	6.5
ENS 14 A	14.0	24	175 x 885 x 230	750	11.0
ENS 18 A	18.0	30	175 x 1,050 x 230	960	13.0



STULZ UltraSonic BNB humidifiers for direct room humidification

Units from the STULZ UltraSonic BNB 1000 A to BNB 8000 A model series are especially suitable for direct room humidification. The principal components of this unit are made of stainless steel or high-grade plastic. A fan integrated in the housing distributes the cold mist, which is generated in the water bath, around the room. Tried and tested controller components ensure that the

desired room humidity is precisely maintained. This unit is used to humidify production rooms, computer rooms, storage facilities, printing plants, museums, restoration workshops, theaters, and many other areas in which optimum humidity is essential for production, storage or the room climate.



BNB direct room humidifiers


Model	Humidifier capacity (kg/h)	Number of oscillators	Dimensions H x W x D (mm)	Power consumption (W)	Air throughput (m ³ /h)	Weight without water (kg)
BNB 1000 A	1.0	2	255 x 254 x 200	100	72	7.1
BNB 2000 A	2.0	4	255 x 364 x 200	180	108	9.3
BNB 3000 A	3.0	6	255 x 474 x 200	250	144	11.2
BNB 4000 A	4.0	8	255 x 584 x 200	340	216	14.0
BNB 5000 A	5.0	10	255 x 694 x 200	430	252	16.1
BNB 8000 A	8.0	16	255 x 1,024 x 200	670	396	23.0



STULZ UltraSonic SCA and FN humidifiers with distribution system

STULZ UltraSonic SCA and FN humidifying systems were developed for special applications requiring pinpoint humidification. The SCA system features a universal distribution system, which is able to supply humidifying


mist to fresh food counters and climatic chambers, for example. And the compact FN models were designed for installation in air conditioning units, laboratory cabinets, automated brewing systems, ventilation cabinets, etc.



BNB direct room humidifiers

Model	Humidifier capacity (kg/h)	Number of oscillators	Dimensions H x W x D (mm)	Power consumption (W)	Air throughput (m ³ /h)	Weight without water (kg)
SCA 1000 A	1.0	2	195 × 272 × 220	100	-	6.0
SCA 2000 A	2.0	4	195 × 272 × 220	160	-	7.0
SCA 1000 AX ¹⁾	0.2 - 1.0	2	195 × 272 × 220	100	-	6.0
SCA 2000 AX ¹⁾	0.2 - 2.0	4	195 × 272 × 220	160	-	7.0
FN 400 HDA	0.4	1	95 × 158 × 90	40	-	1.7

The right humidification solution for every project



STULZ UltraSonic-Controller USM/USS – the universal control solution. The STULZ UltraSonic-Controller is integrated in a master-slave control solution that enables up to 15 humidifiers to be actuated. For each humidifying system, only one controller with plain text display for setpoint input, display of control actual values and error messages is required in the USM master control unit. All other humidifiers in the system are controlled by the connected USS slave control units. The USM/USS control units can be used to regulate the humidity using humidity sensors based on PI controllers, or for proportional control via an external power request. The various control options also include further electrical inputs/outputs, such as alarm/status signals, remote On/Off, optional water quality monitoring, and a great deal more.

STULZ UltraSonic Interface – integrating the control system in existing MSR peripheral equipment. The STULZ UltraSonic Interface was developed because many projects already feature complex MSR technology, and there is a need to integrate STULZ UltraSonic humidifiers simply and inexpensively. Using an external control signal, up to four STULZ UltraSonic Interface units or STULZ UltraSonic humidifiers can be combined to create an overall system with an output from 0–100 %. The various control options also include further electrical inputs/outputs, such as alarm/status signals, remote On/Off, optional water quality monitoring, and a great deal more.

	STULZ UltraSonic-Controller USM/USS	STULZ UltraSonic Interface
Type of delivery	Wired ready for operation	Packaged loose for installation
Possible type of control	Rel. humidity / proportional / On-Off	Proportional / On-Off
Possible connection of humidity sensors	Yes, up to two humidity sensors	No
Hygienic flushing to VDI 6022	Yes, external flush valve required	Yes, external flush valve required
Master-slave circuit	Synchronous control of up to 15 STULZ UltraSonic units	Cascade control of up to 4 STULZ UltraSonic units
Digital inputs	Remote On/Off, external enable, optional water quality monitoring	External enable, optional water quality monitoring, error reset
Digital outputs	Collective alarm, status signal, external flush valve	Collective alarm, status signal, external flush valve

STULZ Company Headquarters

STULZ GmbH

Holsteiner Chaussee 283
22457 Hamburg
Tel. +49 40 5585-0
products@stulz.de

STULZ Subsidiaries

GERMANY
AUSTRALIA
AUSTRIA
BELGIUM
BRAZIL
CHINA
FRANCE
INDIA
INDONESIA
ITALY
MEXICO
NETHERLANDS
NEW ZEALAND
POLAND
SINGAPORE
SOUTH AFRICA
SPAIN
SWEDEN
UNITED KINGDOM
USA

STULZ Australia Pty. Ltd.

34 Bearing Road
Seven Hills NSW 2147
Tel. +61 (2) 96744700
sales@stulz.com.au

STULZ Austria GmbH

Industriezentrum NÖ – SÜD,
Straße 15, Objekt 77, Stg. 4, Top 7
2355 Wiener Neudorf
Tel. +43 1 615 99 81-0
info@stulz.at

STULZ Belgium BVBA

Tervurenlaan 34
1040 Brussels
Tel. +32(470)292020
info@stulz.be

STULZ Brasil

Ar Condicionado Ltda.
Rua Cancioneiro de Évora, 140
Bairro - Santo Amaro São
Paulo-SP, CEP 04708-010
Tel. +55 11 4163 4989
comercial@stulzbrasil.com.br

STULZ Air Technology and Services Shanghai Co., Ltd.

Room 406, Building 5
457 North Shanxi Road
Shanghai 200040
Tel: + 86 21 3360 7101
info@stulz.cn

STULZ France S. A. R. L.

107, Chemin de Ronde
78290 Croissy-sur-Seine
Tel. +33(1)34 80 47 70
info@stulz.fr

STULZ-CHSPL (India) Pvt. Ltd.

006, Jagruti Industrial Estate
Mogul Lane, Mahim
Mumbai - 400016
Tel. +91 (22) 56 66 94 46
info@stulz.in

PT STULZ Air Technology Indonesia

Kebayoran Square blok KQ unit A-01
Jalan Boulevard Bintaro Jaya,
Bintaro Sektor 7,
Tangerang Selatan 15229
Tel. +62 21 2221 3982
info@stulz.id

STULZ S.p.A.

Via Torricelli, 3
37067 Valeggio sul Mincio (VR)
Tel. +39(045)633 1600
info@stulz.it

STULZ México S.A. de C.V.

Avda. Santa Fe No. 170
Oficina 2-2-08, German Centre
Delegación Alvaro Obregon
MX- 01210 México
Distrito Federal
Tel. +52(55)52928596
ventas@stulz.com.mx

STULZ GROEP B. V.

Postbus 75
180 AB Amstelveen
Tel. +31(20)5451 111
stulz@stulz.nl

STULZ New Zealand Ltd.

Unit O, 20 Cain Road
Penrose, Auckland 1061
Tel. +64(9)360 32 32
sales@stulz.co.nz

STULZ Polska SP. Z O.O.

Budynek Mistral.
Al. Jerozolimskie 162
02 – 342 Warszawa
Tel. +48(22)883 30 80
info@stulz.pl

STULZ Singapore Pte Ltd.

1 Harvey Road
#04-00 Tan Heng Lee Building
Singapore 369610
Tel. +65 6749 2738
sales@stulz.sg

STULZ South Africa Pty. Ltd.

Unit 3, Jan Smuts Business Park
Jet Park, Boksburg
Gauteng, South Africa
Tel. +27(0)11 397 2363
aftersales@stulz.co.za

STULZ España S.A.

Calle Carabaña, 25C
28925 Alcorcón (Madrid)
Tel. +34(91)517 83 20
info@stulz.es

STULZ Sverige AB

Västertorpsvägen 135
129 44 Hägersten
Stockholm, Sweden
Tel. +46 8 12157550
info@stulzverige.se

STULZ U. K. Ltd.

First Quarter,
Blenheim Rd. Epsom
Surrey KT 19 9 QN
Tel. +44(1372)74 96 66
sales@stulz.co.uk

STULZ AIR TECHNOLOGY SYSTEMS (STULZ USA) , INC.

1572 Tilco Drive
Frederick, MD 21704
Tel. +1(301)620 20 33
info@stulz-ats.com


Technical data subject to change without notice. 1100119 V1.2 11-18 en · © STULZ GmbH, Hamburg

Close to you around the world

With specialist, competent partners in ten German branches and in subsidiaries and exclusive sales and service agents around the world.

Our ten production sites are situated in Europe, North America and Asia.

For further information, please visit our website at www.stulz.com



You can find out more
on our product page.